



City Research Online

City St George's, University of London

Citation: Slingsby, A., Hyde, J. & Turkay, C. (2019). Visual Analysis of Reactionary Train Delay from an Agent Based Model. Poster presented at the EuroVis 2019, 3-7 Jun 2019, Porto, Portugal. doi: 10.2312/eurp.20191153

This is the published version of the paper.

This version of the publication may differ from the final published version. To cite this item please consult the publisher's version.

Permanent repository link: <https://openaccess.city.ac.uk/id/eprint/22460/>

Link to published version: <https://doi.org/10.2312/eurp.20191153>

Copyright and Reuse: Copyright and Moral Rights remain with the author(s) and/or copyright holders. Copies of full items can be used for personal research or study, educational, or not-for-profit purposes without prior permission or charge, unless otherwise indicated, provided that the authors, title and full bibliographic details are credited, a hyperlink and/or URL is given for the original metadata page and the content is not changed in any way. For full details of reuse please refer to [City Research Online policy](#).

Visual Analysis of Reactionary Train Delay from an Agent Based Model

Aidan Slingsby¹, Jonathan Hyde² and Cagatay Turkey¹



¹giCentre, City, University of London, UK; ²Risk Solutions, UK.



Problem

Reactionary ("knock-on") delay is an increasing problem for UK train operators and is hard to understand. Train operators want to know the key locations and reasons, so they can design interventions.

What is reactionary delay?



Our approach

We build an Agent Based Model that explicitly models interactions between trains, then design interactive visualisation to help understand the problem to inform designing interventions. We can then run the model again to see if this works.

Agent Based Model

The agent-based model stochastically generates primary delays (including small natural variation) according to historical data, the interactions between trains and the resulting reactionary delay. The model runs 150 times (Monte-Carlo style) and it generates thousands of delays for hundreds of trains.

Interactive visualisation


Our interactive visualisation takes the model's output and [A] provides the association between primary and reactionary delay location, [B] gives the uncertainty around this result through model run agreement, and [C] explains the mechanism of the chain of delays.

[A] Association between primary and reactionary locations

The matrix shows the association between locations where primary delays occur (columns) and where the resulting reactionary delays (rows) occur.

Blue shading is the number of primary delay minutes - here it is more than the resulting reactionary minutes

rows are locations where reactionary delays occur, ordered by total reactionary delay




columns are locations where primary delays occur, ordered by amount of reactionary they cause

Each cell is a primary-reactionary delay location pair

Red shading is the number of reactionary delay minutes - here it was caused by a smaller amount of primary delay minutes

All primary delay is "subthreshold"



Bars are total number of primary delay minutes

Delay types by proportion of primary delay minutes for mouseovered location ("EALINGB") - see bottom for colour key

[B] Uncertainty, through comparison of model runs

Looking at the variation between model runs indicates the certainty (or likelihood) of that outcome

As left, but width indicates proportion of model runs that generate a delay

Most model runs indicate "subthreshold" primary delay



Each vertical bar is a model run, its width is the primary delay minutes and the relative proportions of delay type shown in the bar.

Most model runs indicate "reactionary" causing delay, but a minority of runs attribute this to "subthreshold" and "offNetwork"

"Reactionary" and "offNetwork" both feature in most model runs, but occur in different amounts, but "track" and "network" only happen in some model runs.

[C] Explain mechanism of reactionary delay chains

Looking at the interaction between trains helps understand what kinds of interventions may be effective.



Map of the route between London (East) and Bristol (West)

The blue bars are the primary delay minutes that cause the reactionary delay at "EALINGB" where the mouse cursor is

Red arrow shows the reactionary location where the mouse pointer is ("EALINGB"). (If on a cell, it would additionally show a blue arrow).

colour legend for primary delay types (colour scaled to)



risksolutions
leave nothing to chance

