

## City Research Online

### City, University of London Institutional Repository

**Citation:** Rüppel, B., Weiß, L., Karathanassis, I. K., Smith, T., Gavaises, M. & Wensing, M. (2025). Investigation of Immersion Cooling in Battery Packs with PIV and Simultaneous Heat Flux Measurement in an Optical Oil Flow Channel. International Conference on Fluid Flow, Heat and Mass Transfer, doi: 10.11159/ffhmt25.150 ISSN 2369-3029 doi: 10.11159/ffhmt25.150

This is the published version of the paper.

This version of the publication may differ from the final published version.

**Permanent repository link:** https://openaccess.city.ac.uk/id/eprint/36077/

Link to published version: https://doi.org/10.11159/ffhmt25.150

**Copyright:** City Research Online aims to make research outputs of City, University of London available to a wider audience. Copyright and Moral Rights remain with the author(s) and/or copyright holders. URLs from City Research Online may be freely distributed and linked to.

**Reuse:** Copies of full items can be used for personal research or study, educational, or not-for-profit purposes without prior permission or charge. Provided that the authors, title and full bibliographic details are credited, a hyperlink and/or URL is given for the original metadata page and the content is not changed in any way.

City Research Online: <a href="http://openaccess.city.ac.uk/">http://openaccess.city.ac.uk/</a> <a href="publications@city.ac.uk/">publications@city.ac.uk/</a>

Proceedings of the 12<sup>th</sup> International Conference on Fluid Flow, Heat and Mass Transfer (FFHMT 2025) July 15, 2025 - July 17, 2025 | Imperial College London Conference, London, United Kingdom

Paper No. 150

DOI: 10.11159/ffhmt25.150

# Investigation of Immersion Cooling in Battery Packs with PIV and Simultaneous Heat Flux Measurement in an Optical Oil Flow Channel

# Bastian Rüppel<sup>1,2</sup>, Lukas Weiß<sup>1,2</sup>, Ioannis K. Karathanassis<sup>3</sup>, Timothy Smith<sup>4</sup>, Manolis Gavaises<sup>3</sup>, Michael Wensing<sup>1,2</sup>

<sup>1</sup>Professorship for Fluid Systems Technology, Friedrich-Alexander Universität Erlangen-Nürnberg (FAU)

Cauerstraße 4, 91058 Erlangen, Germany

<sup>2</sup>FAU, Erlangen Graduate School in Advanced Optical Technologies (SAOT)

Paul-Gordan-Str. 6, 91052 Erlangen, Germany

<sup>3</sup>City St George's, University of London

Northampton Square, London EC1V 0HB, United Kingdom

<sup>4</sup>Lubrizol European Research and Development Centre

Nether Lane, Hazelwood, DE56 4AN Derby, United Kingdom

bastian.rueppel@fau.de

### **Extended Abstract**

We combine flow investigations with particle image velocimetry (PIV) and simultaneous heat flux measurement across the surface of real battery modules using the atomic layer thermopile (ALTP) technique in a new optical oil flow channel. It represents the dimensions of a realistic immersion cooled battery pack. The objective is to compare the cooling performance of different oils, where some received viscoelastic properties through additives. In previous studies, we performed characterization that is more fundamental in benchmark geometries [1].

The channel cross section is of rectangular shape with a height of 100 mm and width of 47.5 mm. Along the main flow direction, there are four battery cells of 147 mm length lined up with a spacing of 27.5 mm. They cover the height of the channel. On both sides, a gap of 10.4 mm remains. The channel walls are made from acrylic glass, allowing for optical access. We perform time-resolved two-dimensional two-component PIV with a high-speed camera. We vary the flow conditions in terms of Reynolds numbers.

Through a closed flow loop, we secure and survey the upstream temperature of the oil. We charge and discharge the batteries at different rates to reproduce realistic thermal loads. An electric load monitors the output voltage and current. Additionally, we position ALTP sensors on the side faces of the cell, where the heat transfer to the oil takes place. The sensors facilitate direct measurement of the heat flux, obviating the necessity to calculate it from temperatures and to base this calculation on assumptions. In a recent study, we demonstrate the experimental principle in a benchmark case [2]. Each sensor is of rectangular shape with an active area of 100 mm x 8 mm. Additionally we employ dummy cells, which we can heat in a controlled and reproducible manner. There the heating rates can significantly exceed the rates that results from charging and discharging the real cells. We compare our experimental results to computational fluid dynamics (CFD). Karathanassis et al. recently reported preliminary results from related simulations [3].

The new flow channel allows us to conclude the preparative, fundamental work we did on heat transfer in viscoelastic oils. By including and discharging the batteries, we take a big step closer to the real-world application.

#### References

- [1] Weiß, L., Rüppel, B., Weiß, T., & Wensing, M. (2024). Cross-plane PIV for the characterization of low viscosity viscoelastic fluids. In *Proceedings of the 21st LISBON Laser Symposium 2024*. Lisbon.
- [2] Weiß, L., Karathanassis, I.K., Rüppel, B., Smith, T., & Wensing, M. (2024). Enhancing Heat Transfer in Immersion Cooling of Battery Packs Using ALTP Heat Flux Sensors. In *Proceedings of the Energy & Propulsion Conference & Exhibition*. Columbus, US: SAE Mobilus.
- [3] Karathanassis, I.K. (2024), Design and Characterization of Environmentally-Friendly Heat Transfer Liquids for Electric-Vehicle Battery Packs. In *STLE Annual Meeting 2024*. Minneapolis, US.